

{{customTxt}}

Hyster H1.5-3.5XT XT Series Internal Combustion Counterbalanced Forklift - Forklift Truck



SKU:OME-ENG-190236-0249

Price not available for this product / service.

Please click on 'MAKE AN INQUIRY' and send us an inquiry to direct your requirement to the supplier to receive pricing and further information.

Quick Overview

- Ergonomically designed operator compartment
- Advanced LCD dash display
- Hyster stability mechanism
- Hydrostatic steer axle
- Removable floor plate
- Heavy-duty drive axle

Details

Hyster H1.5-3.5XT XT Series Internal Combustion Counterbalanced Forklift - Forklift Truck

THE POWERFUL ADDITION FOR PEAK MATERIALS HANDLING PERFORMANCE

Hyster H1.5-3.5XT Internal Combustion Counterbalanced lift trucks offer breakthrough forklift solution which sets the standard for quality, dependability and operational efficiency, boasting the lowest cost of ownership, maximum uptime, operator preferred ergonomics and unmatched performance

Delivering the perfect combination of power, speed, low fuel consumption and clean performance, the range has also been designed with operational safety and ease of maintenance in mind.

Hyster H1.5-3.5XT series highlights include:

- Load capacity from 1.5 to 3.5 tones
- Available in petrol, LPG and diesel
- Less maintenance with 500-hour engine service intervals
- Maintenance-free Hyster Stability Mechanism™ system reduces truck lean in turns, improving lateral stability without compromising uneven surface travel
- Exclusive Vista™ Mast with high strength design improves capacity retention at high lifts and delivers excellent visibility and rigidity for this class of truck
- Cooling system with optimized ducting and high volume tunnels allows longer run time in a cooler state, increasing component life and reducing risk of overheating on heavy-duty tasks
- Advanced control and operational functions include Traction Interlock and Hydraulic Interlock safety functions and a side shift feature designed to facilitate maximum visibility for adjusting and aligning loaded goods
- Transmission gear profiles are optimized to reduce operator noise, with an improved gear tooth profile dropping the combined noise level down 2dB and operating in conjunction with isolated powertrain to minimize operator fatigue
- 3-point entry design enables easy entry and exit from both sides and combines with an open non-slip step at optimum height to reduce muscle and joint stress
- Smaller steering wheel, adjustable steering column, improved rear drive handle and low-vibration operator's seat combine for a comfortable and secure operator environment
- Adjustable vertical muffler aims emissions away from the operator in dust-filled environments where exhaust gases may be present
- Best-in-class service access with a one-piece, rear-opening hood providing cowl-to-counterweight access, plus full engine access via removal of the rear panel
- V-ECU and advanced dash display showing state-of-the-art on-board diagnostics and error codes combine to facilitate timely and accurate service and repairs

Specs

Criteria	Details						
Model	H1.5XT	H1.8XT	H2.0XTS	H2.0XT	H2.5XT	H3.0XT	H3.5XT

Load Capacity (KG)	1500	1750	2000	2000	2500	3000	3500
Load Centre (MM)	500	500	500	500	500	500	500
Lift Height (MM)	3000	3000	3000	3000	3000	3000	3000
Turning Radius (MM)	1960	1995	2030	2185	2245	2365	2415